

PRODUCT INFORMATION

Model Revision

Bio Bull CS Compact Pto 12-2024



Operator/driving force

Hydraulic drive of conveyor and cloth roll. The machine is equipped with **2** hydraulic pumps operating in separate systems.

Benefits:

- 2 pumps prevent unwanted speed differences when you are entering and cloth rolling.
- Directly driven pumps ensure a compact construction and no maintenance costs.
- Danfoss hydraulic control valves for proper and smooth operation of the machine.

Pto drive of the choppercage. Can be connected left and right.



Infeed unit

Infeed unit for cloth up to 200 meters. Infeed width 600 mm.



Chopper-unit with input unit

Chopper unit 600 mm with V-blades which have a grinding attachment.

Benefits:

- Robust cutting chamber and importation unit for a long service life.
- Low maintenance and repairs.
- Spare parts of the cage and importation unit available almost everywhere in the world.
- Sustainability already proven in maize and grass choppers.



Outfeed belt



Benefits:

- Sustainable outfeed of any product no matter humidity and weight.

Control panel

Remote control of the machine, system Danfoss.

Benefits:

- Operation is always possible from the place with the most visibility and is therefore safe.
- The machine is operated by remote control allowing you to stay out of the danger zone of the machine.
- Danfoss is known worldwide, highly durable and trouble-free.

Chassis

4 massive wheels

Dimensions

Machine dimensions approximate:

- Width 2.0 meters.
- Height 2.0 meters.
- Length 2.0 meters.
- Weight +/- 2.500 kg.
- Canvas width up to 1400 mm.

Capacity

Up to 5.000 m² per hour.

Optional

- Metal detector.
- Infeed screw recommended with soft fruit.

COC:

VAT:

Bank:

BIC:

93652291

RABONL2U

NL866481382B01

NL28RABO 0189 5216 43