



## PRODUCT INFORMATION

### **Model**

Bio Bull CS Robust 160

### **Revision**

12-2024




### **Motor**

Stage 3 engine: John Deere industrial engine 165 hp at 2000 rev/min common rail diesel

Stage 5 engine: John Deere industrial engine 173 hp at 2000 rev/min common rail diesel

Benefits of this engine:

- Low fuel consumption.
- Worldwide service network of John Deere.



**Bio Bull Crop Rotation B.V.**  
Lodderhoeksestraat 14  
6687 LS, Angeren  
The Netherlands

[www.bio-bull.com](http://www.bio-bull.com)  
[info@bio-bull.com](mailto:info@bio-bull.com)  
+31 621 298 920

**COC:** 93652291  
**VAT:** NL866481382B01  
**Bank:** NL28RABO 0189 5216 43  
**BIC:** RABONL2U



### Operator/driving force

Hydraulic drive of conveyor and cloth roll. The machine is equipped with 2 LS pumps operating in separate systems.

### Benefits:

- 2 pumps prevent unwanted speed differences when you are entering, cloth rolling and emptying the bulk hopper at the same time.
- Directly driven pumps ensure a compact construction and no maintenance costs.
- Danfoss hydraulic control valves for proper and smooth operation of the machine.

### Infeed table

Importation table with on both sides a roll-up unit for cloth up to 200 meters. The diablo rollers over which the canvas runs are hydraulically foldable. High ridges on the elevator belt will rise up for the good upwards conveying of the product. Guided strings left and right ensure always straight running of the tires.



### Chopper unit with input unit

Bio Bull chopping reel with V-blades including semi-automatic grinding system..

The cutting reel will be activated by means of an hydraulic clutch. Outfeed of the crop goes through a conveyor with PVC conveyor belt which is hydraulic adjustable in height. Outfeed with separate remote control function.

### Benefits:

- Robust cutting chamber and importation unit for a long service life.
- Low maintenance and repairs.
- Spare parts of the cage and importation unit available almost everywhere in the world.
- Sustainability already proven technology.
- Easy to access for maintenance



## Bulk hopper

Bulk hopper with PVC conveyor incl. unloading through remote control.



## Control panel

Remote control of the machine, system Hetronic.

### Benefits:

- Operation is always possible from the place with the most visibility and is therefore safe.
- The machine is operated by remote control, allowing you to stay out of the danger zone of the machine.
- Hetronic is known worldwide, highly durable and trouble free.



## Chassis

VTS undercarriage with rubber tracks and 2 driving speeds.

## Dimensions

Machine dimensions approximate:

- Width caterpillar's exterior frame about 2.4 meters.
- Height 2.2 meters.
- Length 6.5 meters.
- Weight +/- 8.000 kg.

## Capacity

Up to 12 000 m<sup>2</sup> per hour.

## Optional

- Automatic lubrication system.
- Metal detection
- Cleanfix fan.

**Bio Bull Crop Rotation B.V.**  
Lodderhoeksestraat 14  
6687 LS, Angeren  
The Netherlands

[www.bio-bull.com](http://www.bio-bull.com)  
[info@bio-bull.com](mailto:info@bio-bull.com)  
+31 621 298 920

**COC:** 93652291  
**VAT:** NL866481382B01  
**Bank:** NL28RABO 0189 5216 43  
**BIC:** RABONL2U